

'using Object Repository

```
WpfWindow("HP MyFlight Sample Application").WpfEdit("agentName").Set DataTable("agentName", dtLocalSheet)
WpfWindow("HP MyFlight Sample Application").WpfEdit("password").SetSecure DataTable("password", dtLocalSheet)
WpfWindow("HP MyFlight Sample Application").Check CheckPoint("chpt_LoginLogo")
WpfWindow("HP MyFlight Sample Application").WpfButton("OK").Click
```

'inline Descriptive Programming

```
WpfWindow("regexpwndtitle:=HP MyFlight Sample Application").WpfEdit("devname:=agentName").Set DataTable("agentName", dtLocalSheet)
WpfWindow("regexpwndtitle:=HP MyFlight Sample Application").WpfEdit("devname:=password").SetSecure DataTable("password", dtLocalSheet)
WpfWindow("regexpwndtitle:=HP MyFlight Sample Application").WpfButton("devname:=okButton").Click
```

'object based Descriptive Programming

'define objects:

```
Set MFApp = Description.Create()
    MFApp("regexpwndtitle").Value = "HP MyFlight Sample Application"
    MFApp("wpftypename").Value = "window"
Set MFAgentName = Description.Create()
    MFAgentName("devname").Value = "agentName"
Set MFPassword = Description.Create()
    MFPassword("devname").Value = "password"
Set MFOk = Description.Create()
    MFOk("devname").Value = "okButton"
```

'script tasks:

```
WpfWindow(MFApp).WpfEdit(MFAgentName).Set DataTable("agentName", dtLocalSheet)
WpfWindow(MFApp).WpfEdit(MFPassword).SetSecure DataTable("password", dtLocalSheet)
WpfWindow(MFApp).WpfButton(MFOk).Click
```

'clean-up

```
Set MFApp = Nothing
Set MFAgentName = Nothing
Set MFPassword = Nothing
Set MFOk = Nothing
```